

# USB Video Capture

## iGrabber Pro

# Geniatech



Video capture card, can capture high quality video and audio through USB. Plug and Play, no need to install driver and external power, can be used on PC or laptop computer. The main feature of this device is to capture TV, DVD, camera and other similar devices' high quality video and audio to computer. User can copy and edit the captured file on the PC, it can also work as home security camera if a camera is connected. iGrabber Pro is the new USB2.0 video capture device, with the multimedia decoder chipset, it gives you more clear, more smooth video and give you high quality audio without soundcard.

- Driver Free plug and play
- Easy to use, One button to start/stop recording
- Convert Analog video to Digital video (Resolution: NTSC: 720x480 PAL: 720x576, Max frame rate: NTSC: 30fps PAL: 25fps)
- Support third-party video capture program: OBS, VHS, Quicktime, Amcap, VLC, Wirecast, XSplit etc.
- Support Mac ,Android and Windows , Linux OS
- Fine tuned Software and Hardware, CPU/memory usage reduce to the lowest



## Product Features

- USB2.0 connector, support plug and play, support laptop computer
- Contains A/V input and S-Video input.
- Max resolution: NTSC: 720x480 PAL: 720x576
- 1.5Mbps high quality video
- Max frame rate: NTSC: 30fps PAL: 25fps
- Support USB Audio capture, stereo input
- No driver needed
- Fine tuned Software and Hardware, CPU/memory usage reduce to the lowest
- Can capture high quality dynamic and static screen, capture video smoothly and uninterrupted

## Product Applications

- Real-time video and audio capture
- Real-time network (LAN & Internet) video playback
- Multi-point video conferencing
- Home or company use video capture
- Remote network monitoring and remote network TV
- Support OS: Android, Mac, Windows XP/7/8/10, Linux

## I/O Interface

USB output	1x USB2.0
Video/Audio input	1x A/V(Composite)
Video/Audio input	1x S-Video

## Mechanical

Dimension	104 x 34.85 x 14.87mm (4.1" x 1.4" x 0.59")
Weight	75g
Environment	Operating Temp.0~50°C Storage Temp.-20°C to 60°C Humidity:10 to 85%
Certification	CE/FCC