

深圳金亚太科技有限公司

Shenzhen Geniatech Co.,Ltd.

SPECIFICATION

MODEL:APC680



APPROVED BY GENIATECH		
PREPARED BY 编写	CHECKED BY 审核	APPROVED BY 批准

Please return the original copy after approved by your company with seal and signature.
请在贵公司盖章并签字后寄回正本一份。

APPROVED BY CUSTOMER		
COMMENTS 确认意见	APPROVED BY 批准签字	COMPANY SEAL 盖章

Website: www.geniatech.com
Address: Room 02-04, 10 / F, Block A, Building 8, Shenzhen International Innovation Valley,
Dashi Road, Nanshan District, Shenzhen, Guangdong, China

CONTENT

1.GENERAL DESCRIPTION.....	1
2.PRODUCT PICTURE.....	1~2
3.FEATURES.....	3
4. Support FORMATS.....	4
5. PRECAUTIONS FOR USE	4

Revision History

VERSION	DATE	BOARD ID	PAGE	DESCRIPTION	AUTHOR
V1.0	2022/03/16	APC390K	4		

1. GENERAL DESCRIPTION

APC680 is an TV playing box with below new features:

- (I) VS680 Quad-Core Arm® Cortex® A73 processor with SecurityExtensions
- (II) OpenGL® ESTM 1.1/2.0/3.0/3.1/3.2/DirectFB/OpenCLrM 1.2 / Vulkan® 1.1.
- (III) NPU supports INT8/INT16/FP16/BFP16 MAC hybrid operation
- (IV) Android 12.0 / Linux ubuntu OS
- (V) Support 4GB/8GB/16GB LPDDR4
- (VI) 8G~128GB eMMc flash, external expansion storage TF card (Max 512G)
- (VII) GTIOT (Support Z-WAVE / ZIGBEE / LoRa / LTE / GPS / BT5.0)
- (VIII) Support 4G networks (Optional)
- (IX) Built-in WiFi(2.4G/5.8G) /BT4.1 (BT5.0 Optional)
- (X) 10/100/1000M LAN interface
- (XI) 1 * HDMI In, 1 * HDMI Out, support 4K video play
- (XII) 2 * USB Type-A (1*USB3.0+1*USB2.0)
- (XIII) WatchDog&RTC

2. PRODUCT OVERVIEW

Below picture is for reference only, please prevail in kind.





No.	Name	Description
1	Power Key	1 * Power key
2	IR reception	1 * IR reception
3	NET LED	1 * NET LED(Orange)
4	Micro SIM	1 * Micro SIM
5	Power LED	1 * Power LED(Red / Blue)
6	USB 2.0	1 * USB 2.0
7	USB 3.0	1 * USB 3.0
8	HDMI IN	1 * HDMI IN
9	LAN	1 * RJ45
10	HDMI OUT	1 * HDMI OUT
11	DC IN	1 * DC IN

3.FEATURES

CHIPSET		VS680	
OSD LANGUAGE		English/Chinese (multi language OSD)	
Processor	OS	Android 12/Linux	
	CPU	Quad-Core Arm® Cortex® A73 processor with SecurityExtensions	
	GPU	Imagination™ PowerVR™Series9XE GE9920 OpenGL® ESTM 1.1/2.0/3.0/3.1/3.2/DirectFB/OpenCLrM 1.2 / Vulkan® 1.1	
	NPU	supports up to 6.75 TOPs(INT8)/1.69 TOPs(INT16) learning applications operation	
	LPDDR4	4GB (4/8/16GB Optional)	
	EMMC FLASH	16GB (8~128G Optional)	
NETWORK	Ethernet	RJ45, 10/100/1000M	
	WiFi	IEEE 802.11a/b/g/n/ac,2X2 MIMO	
	Bluetooth	BT4.1 (BT5.0 Optional)	
	3G/4G	1* Mini PCIE +1*Micro SIM(Optional)	
WatchDog&RTC		support	
GTIOT		Support Z-WAVE / ZIGBEE / LoRa / LTE / GPS / BT5.0(Optional)	
Interface	HDMI IN	1 * HDMI IN	
	HDMI OUT	1 * HDMI OUT	
	USB 3.0	1 * USB 3.0	
	USB 2.0	1 * USB 2.0(OTG)	
	LAN	1 * RJ45(LED)	
	SIM	1 * Mini pcie LTE(built-in) + 1 * Micro SIM	
	IR	1*IR blaster	
	DC IN	1 * DC IN	
	Power	1 * Power Key	
Adapter		DC12V / 1.5A (Φ5.5mm / φ2.1mm)	
Accessory		1 * Adapter (AC 100 ~ 240V 50/60Hz)	
Size(mm)		106*100*25	
Customizable GUI		We provided GUI customization and we have a vast collection of Launcher created by our R&D team for you to choose from.	

4.Precautions for use

- 1.Relative humidity: $\leq 85\%$.
- 2.CPU Operation temperature: $0\sim 85^{\circ}\text{C}$
- 3.Storage temperature: $-10\sim +60^{\circ}\text{C}$
- 4.Operation temperature: $0\sim +60^{\circ}\text{C}$
- 5.Do not squeeze、distort or disassemble the PC.
- 6.Keep the Board away from static electricity .
- 7.Keep the Board away from water and other liquid.
- 8.Don't use long connect wires which may affect performance and image quality.